

HOLTER analysis system



CLINIC,
DEPARTMENT AND
ENTERPRISE –
SOLUTIONS
FOR ALL
HOLTER NEEDS

H-SCRIBE

P R O D U C T F E A T U R E S

- **Solutions for all Holter Needs** –
H-Scribe offers solutions for the private physician's office as well as multi-facility hospital installations, with 3-channel and 12-lead systems, from stand-alone configurations to networked systems with interface options.
- **Multiple Scanning Options** –
Retrospective, Prospective and Superimposition scanning modes supported to enable both traditional and advanced scanning options.
- **Advanced VERITAS Signal Processing** –
Mortara's VERITAS signal processing algorithms provide superior accuracy in beat detection, labeling and noise rejection resulting in improved identification of events and faster scanning of records.
- **Up to 48-hour Recording** –
Mortara H12+ and H3+ digital Holter recorders can record up to 48 hours of data with only one battery.
- **Networking Solutions** –
Optional remote download and review of Holter data from various sites to support central Holter scanning system with satellite clinics.
- **Interface Export** –
Optional export of the final report in PDF and XML format that enables connectivity to data management systems.

H - S C R I B E [™] H O L T E R S Y S T E M

Feature	Specifications
CPU	Pentium class tower
Operating System	Windows™
Monitor	Color monitor, 1280 x 1024 resolution
Scanning Modes	Retrospective, prospective and superimposition scanning with automatic scan, event review, template review, and page mode capabilities. A customizable user profile allows each operator to configure their scanning preferences
Trend Graphs	HR, RR interval, RR variance, 12-lead ST, SVPB, VPB
Beat Classification	Normal, ventricular, paced, supraventricular, R on T and artifact with color-coded ECG
Rhythm Analysis	Tachycardia/bradycardia, min/max heart rate, Ventricular singles, couplets, runs (longest and fastest); supraventricular singles, couplets, runs (longest and fastest); atrial fibrillation (percentage per hour and summary); pause; longest RR; RR standard deviation; time domain HRV
ST Segment Measurement	3 or 12-lead ST segment measurement, max ST depression, max ST elevation, 3 or 12-lead trends
Pacemaker Analysis	Atrial, ventricular and dual pacemaker detection; capture failure, oversensing, undersensing
Diary Events	Configurable diary entry labels with automatic stop during the scan
Report Options	Patient information; scan criteria (SVPB prematurity, ST segment elevation/depression, long RR/pause); tabular or narrative summary statistics; 24 hour profile; trend and strip pages; full disclosure; user defined acronyms for comments
Data Download	USB download (Mortara H3+), Digital Compact Flash (Mortara H-12 and H12+), 1 mm/sec cassette tape
Download/Scan time	Approx. 90 seconds for 24-hour recordings
Internal Storage	99 full-disclosure recordings
Full Disclosure Archive	DVD+RW
Final Report Export	Optional export in PDF and XML format
Power Requirements	100-240 VAC at 50/60 Hz

*Specifications subject to change without notice.

S T A N D A R D A C C E S S O R I E S

- Mouse, Keyboard
- User Manual

Warranty and Service

Mortara Instrument is committed to the highest level of customer support. Please contact us for the program which will be best suited for your needs.

Mortara Instrument, Inc.
7865 North 86th Street
Milwaukee, WI 53224
Tel: 414.354.1600
Tel: 800.231.7437
Service: 888.MORTARA
Fax: 414.354.4760

Mortara Rangoni Europe, Srl
(European Headquarters, Italy)
Via Cimarosa 103/105
40033 Casalecchio di Reno (BO)
Tel: +39.051.298.7811
Fax: +39.051.613.3582

Mortara Instrument GmbH
(Germany)
Kaninenberghöhe 50
45136 Essen
Tel: +49.201.268311
Fax: +49.201.268313

Mortara Instrument B.V.
(The Netherlands)
H. Dunantplein 6
3731 CL De Bilt
Postbus 131
3720 AC Bilthoven
Tel: +31.30.2205050
Fax: +31.30.2201531

 **Mortara INSTRUMENT**
The World Leader in ECG Technology

<http://www.mortara.com>
ISO 13485 Certified